

AERUS

Protecting Indoor Air and Surfaces™



Features ActivePure Technology proven to reduce viruses, bacteria, and other pathogens (full list of tested pathogens available below in “The Proof”)

THE TECHNOLOGY

The Aerus® Beyond Guardian Air combines multiple complementary technologies, including HEPA, activated carbon, and ActivePure Technology. Patented ActivePure Technology is an advanced surface and air purification technology. It has been proven to reduce over 99.9% of many common airborne and surface contaminants (list of tested pathogens can be found in “The Proof” section below).

ActivePure Technology does not replace the need to follow public health guidelines and should be used as complementary technology.

THE PROOF

In extensive unaffiliated lab testing, ActivePure® Technology has been proven to significantly reduce the following contaminants and pathogens¹:

- SARS-CoV-2
- Staphylococcus Aureus
- Aspergillus niger endospores
- H1N1 Influenza
- H5N8 Influenza
- MRSA
- Bacillus globigii
- MS2 Bacteriophage
- Staphylococcus epidermidis
- PhiX-174
- Erwinia Herbicola
- Listeria monocytogenes
- Murine Norovirus
- E. coli
- Candida auris
- Botrytis cinerea
- Sclerotinia sclerotiorum
- Legionella pneumophila
- Aspergillus versicolor
- Clostridium difficile
- Salmonella enterica

THE BENEFITS

The Aerus Beyond Guardian Air provides 24/7 surface decontamination and air purification without the use of ozone. It is a proactive and effective solution for your home or business.

- Portable, lightweight device
- No installation – plug-and-play solution
- Easy to use and low maintenance
- Proven effective against many common viruses, bacteria, molds, and fungi¹
- Reduces smoke, allergens, odors, and VOC gases without the use of ozone
- Multiple carbon brushes aid in the capture of contaminants



¹View test results at
Aerusonline.com/Scientific-Proof

Inducted into the
2017 Space Technology
Hall of Fame by
the Space Foundation

BEYOND

GUARDIAN AIR GEN II

SPECIFICATIONS

Product Information	120V: 00727 Model: F159H Model F159H Meets California ozone emissions limit. CARB Certified 230V: 00743 Model: F159I
Technology Included	ActivePure® Technology HEPA Filter Activated Carbon Filter Carbon Brushes
Electrical	Input Voltage: 120 VAC 60 Hz Power Consumption: 23 Watts to 80 Watts Conforms to UL STD 867
Mechanical	Motor: 230 VAC; 0.28 Amp Airflow Rate: 75 CFM - 240 CFM
Weight & Dimensions	34 lbs (15.5 kg) 23" H x 20" W x 11" D (58.4 cm x 50.8 cm x 27.9 cm)
Operating Temperature	(Return Air) 30°F to 95°F (-1°C - 35°C)
Sound Level	Speed 1: 32 dB (A) Speed 2: 39 dB (A) Speed 3: 46 dB (A) Speed 4: 58 dB (A)
Coverage¹	Up to 2,500 sq. ft. (232 m ²) depending on occupant density and other factors ¹ . High density commercial not to exceed 1,000 sq. ft. (92 m ²).
Warranty	Limited 3 Year Warranty



Contact Name: _____



Email: _____



Phone Number: _____

1. Assumes 8 foot ceilings. Solutions should be customized based upon a variety of factors including HVAC system capabilities and settings, air flows taking into account walls, air pressure, and doors, ambient air temperatures and humidities, variable density, known VOC concentrations, and other layers of protection.